

Material Safety Data Sheet

材料安全数据表

Product Name: Rechargeable Lithium Iron Phosphate Battery

产品名称: 可充电磷酸铁锂电池

Model: NHS-1Y10K, NHS-1Y15K, NHS-1Y20K, NHS-1Y25K, NHS-1Y30K,

型号: NHS-1Y35K, NHS-1Y40K

Applicant: Qingdao Nahui Energy Technology Co., LTD.

申请商: 青岛纳晖能源科技有限公司

> Room 303, Entrance 1, No. 4 Building, Lan Gu Entrepreneurship Center Phase 1, No. 7, Keji Yilu Road, Aoshanwei Sub district Office, Jimo District,

Applicant Address:

Qingdao, Shandong, China

申请商地址:

山东省青岛市即墨区鳌山卫街道办事处科技一路7号蓝谷创业中心一期4号楼

1 单元 303 室

Date of Issue: 发行日期:

2024-08-19

Validity of Report

报告有效期:

2024-08-19 ~ 2024-12-31

Prepared By: Dongguan Lepont Testing Service Co., Ltd.

编制单位: 东莞市力邦检测服务有限公司

Room 202, Building 1, No. 65, Jiulong Road, Dongcheng Subdistrict,


Dongguan, Guangdong, China

广东省东莞市东城街道九龙路 65 号 1 栋 202 室

Compiled by (name+ signature)/编写......: Li Zhou

Lieguang Chen Approved by (name+signature)/批准.....:

Test Report Form No.: MSDS-E





Section 1- Identification of the product and supplier

第一部分-产品及供应商标识

Product Name: Rechargeable Lithium Iron Phosphate Battery

产品名称: 可充电磷酸铁锂电池

Model/型号: NHS-1Y10K, NHS-1Y15K, NHS-1Y20K, NHS-1Y25K, NHS-1Y30K, NHS-1Y35K, NHS-1Y40K

Rated Value/额定值: 102.4V, 50Ah, 5.12kWh Manufacturer: Far East Battery Jiangsu Co., Ltd

制造商: 远东电池江苏有限公司

Manufacturer Address: No. 8, Keji Avenue, Gaocheng Town, Yixing City, Wuxi City, Jiangsu Province, P. R.

China

制造商地址: 江苏省无锡市宜兴市高塍镇科技大道八号

Telephone Number/电话: +86-18879553505

Emergency Telephone No. (24h)/紧急联系电话: +86-18879553505

E-mail/邮箱: 134651@600869.com

Supplier:

ΝZ

Company name: FISHER & PAYKEL APPLIANCES LIMITED (43285)

NZBN: 9429040747378

Address: 78 Springs Road East Tamaki Auckland NZ 2013

Telephone/Fax 0800 424 372

Website: https://www.haierhome.co.nz/ Email: FPA CXQ - Home Solutions Tier3

FPA.CXQHomeSolutionsTier3@fisherpaykel.com

ΑU

Company name: FISHER & PAYKEL AUSTRALIA PTY. LIMITED

ABN: 71 000 042 080 Address: QLD 4178

Telephone/Fax 1300 729 948

Website: https://www.haierhome.com.au/ Email: FPA CXQ - Home Solutions Tier3

FPA.CXQHomeSolutionsTier3@fisherpaykel.com



Section 2-Hazards Identification 第二部分-危害识别

Preparation hazards and classification 危害分类	Not dangerous with normal use. Do not dismantle, open or shred the Battery ingredients contained within or their ingredients products could be harmful. 正常使用没有危险,不能拆解、打开或分解电池,里面的材料或成分是有害的		
Appearance, Color, and Odor 外观、颜色及气味	Solid object with no odor, no color. 无色、无味、固态		
Primary Route(s) of Exposure 主要暴露途径	These chemicals are contained in a sealed enclosure. Risk of exposure occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, exposure to the electrolyte solution contained within can occur by Inhalation, Ingestion, Eye contact and Skin contact. 这些化学药品装在密封的容器里。暴露的风险只有在电池受到机械、加热或滥用电时危及外壳才会发生。如果发生这种情况,接触电解液所包含的可能发生吸入、食入、皮肤接触、眼睛接触。		
Potential Health Effects 潜在的健康影响	ACUTE (short term): See Section 8 for exposure controls In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be corrosive and can cause burns. 接触控制请看第 8 章节。在这种情况下,电池破裂,电池中包含的电解液具有腐蚀性,可以引起烧伤。 Inhalation: Inhalation of materials from a sealed battery is not an expected route of exposure. Vapors or mists from a ruptured battery may cause respiratory irritation. 吸入: 从密封电池吸入材料不是预期的接触途径。破裂电池散发出来的气雾会引起呼吸道刺激。 Ingestion: Swallowing of materials from a sealed battery is not an expected route of exposure. Swallowing the contents of an open battery can cause serious chemical burns of mouth, esophagus, and gastrointestinal tract. 食入: 从密封电池中吞咽材料并不是一种预期的接触途径。吞咽破裂电池的组成成分可以引起嘴,食道和胃肠道严重的化学烧伤。 Skin: Contact between the battery and skin will not cause any harm. Skin contact with contents of an open battery can cause severe irritation or burns to the skin. 皮肤: 完整的电池与皮肤接触不会造成任何伤害。皮肤接触了破裂电池内部物质可能引起严重的刺激或烧伤皮肤。 Eye: Contact between the battery and the eye will not cause any harm. Eye contact with contents of an open battery can cause severe irritation or burns to the eye. 眼睛: 完整的电池与眼睛之间的接触不会造成任何伤害。眼睛接触了破裂电池内部物质可能引起严重的刺激或烧伤眼睛。 CHRONIC (long term): See Section 11 for additional toxicological data		
Medical	慢性(长期): 请看第 11 章节 Not applicable		
Conditions Aggravated by Exposure 身体状况因暴露 而恶化	不适用		
Reported as carcinogen	Not applicable 不适用		

Section 3 – Composition/Information on Ingredients 第三部分-主要成分/组成信息

Information about the chemical nature of product/产品的化学性质信息:

Chemical Name	Concentration or concentration	CAS Number
化学名称	ranges (%)	CAS 号(化学文摘索引登记号)
	浓度或浓度范围(%)	
Graphite 石墨	7-25	7782-42-5
Lithium iron Phosphate 磷酸铁锂	15-40	15365-14-7
Hexafluoropropylene-vinylidene		
fluoride Copolymer P875306	3-15	9011-17-0
聚(偏二氟乙烯-co-六氟丙烯)		
Lithium Hexafluorophosphate	0-5	21324-40-3
六氟磷酸锂	0-0	21024-40-0
Carbon Black 炭黑	0-2	1333-86-4
Diethyl Carbonate 碳酸二乙酯	0-15	105-58-8
Dimethyl Carbonate 碳酸二甲酯	0-15	616-38-6
Ethyl Methyl Carbonate 碳酸甲乙酯	0-15	623-53-0
Propylene Carbonate 碳酸丙烯酯	0-15	108-32-7
Other 其它	Remainder	N/A

Labeling according to EC directives.

标签需根据 EC 指令

No symbol and risk phrase are required.

不需要任何符号和风险短语。


Note: CAS number is Chemical Abstract Service Registry Number.

注意:CAS 号是化学文摘服务注册号

N/A=Not applicable/不适用

Section 4 – First-aid Measures 第四部分-急救措施

Inhalation	If contents of an opened battery are inhaled, remove source of contamination or move	
吸入	victim to fresh air. Obtain medical advice.	
	如果吸入了破裂电池内部物质,移除污染源或将受害者移至新鲜空气处,寻求医生建议。	
Ingestion	If ingestion of contents of an open battery occurs, never give anything by mouth if victim	
食入	is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth	
	thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 60 to 240 mL (2-8	
	oz.) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of	






1721	Page 5 of 13
	aspiration. Have victim rinse mouth with water again. Quickly transport victim to an
	emergency care facility.
	如果食入了破裂电池内部物质,受害者正在迅速失去意识,或昏迷或抽搐,千万不要给他
	们任何食物。让患者用水彻底冲洗口腔。不要催吐。让患者喝 60 - 240 毫升(2-8 盎司)的水。
	如果呕吐是自然发生的,请让患者身体前倾,以减少误吸的风险。让患者再次用水漱口。
	迅速将受害者送往急救中心。
Skin contact	If skin contact with contents of an open battery occurs, as quickly as possible remove
皮肤接触	contaminated clothing, shoes and leather goods. Immediately flush with lukewarm, gently
	flowing water for at least 30 minutes. If irritation or pain persists, seek medical attention.
	Completely decontaminate clothing, shoes and leather goods before reuse or discard.
	如果接触到破裂电池的内部物质,应尽快去除被污染的衣服、鞋子和皮革制品。立即用温
	和的流动水冲洗至少30分钟。如果刺激或疼痛持续,立即就医。衣物、鞋及皮具必须彻底
	去污,方可再用或弃置。
Eye contact	If eye contact with contents of an open battery occurs, immediately flush the
眼睛接触	contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes while
	holding the eyelids open. Neutral saline solution may be used as soon as it is available. If
	necessary, continue flushing during transport to emergency care facility. Take care not to
	rinse contaminated water into the unaffected eye or onto face. Quickly transport victim to
	an emergency care facility.
	如果眼睛接触了破裂电池内部物质,立即用温水轻轻流动的水将被污染的眼睛冲洗至少30
	分钟,同时保持眼睑打开。一旦有了中性盐水溶液,可以立即使用。如有必要,在运送到
	急救设施期间继续冲洗。注意不要将受污染的水冲洗到未受影响的眼睛或脸上。迅速将受
	害者送往急救中心。

Section 5 – Fire-fighting Measures 第五部分—消防措施

Flammable	In the event that this battery has been ruptured, the electrolyte solution contain within the	
Properties	battery would be flammable. Like any sealed container, battery cells may rupture when	
易燃的特性	exposed to excessive heat; this could result in the release of flammable or corrosive	
	materials.	
	在电池已经破裂情况下,电池中的电解液中是易燃的。像任何密封容器一样,电池暴露在	
	过热环境下可能会破裂;这可能导致易燃或腐蚀性材料的释放。	

Suitable extinguishing Media	Use extinguishing media suitable for the materials that are burning.
合适的灭火媒	使用适合于正在燃烧的材料的灭火介质。
介	
Unsuitable	
extinguishing	Not available
Media	不适用
不合适的灭火	小坦用
媒介	





	,	
Explosion Data	Sensitivity to Mechanical Impact: This may result in rupture in extreme cases	
爆炸系数	对机械冲击的敏感性: 在极端情况下, 这可能导致破裂	
	Sensitivity to Static Discharge: Not Applicable	
	对静电放电的敏感性: 不适用	
Specific	Fires involving Pattery are centralled with water When water is used however hydrogen	
Hazards arising	Fires involving Battery are controlled with water. When water is used, however, hydrogen	
from the	gas may evolve. In a confined space, hydrogen gas can form an explosive mixture. In this	
chemical	situation, smothering agents are recommended to extinguish the fire	
由化学物质引	涉及电池的火灾是用水控制的。当使用水时,然而可能会产生氢气。在密闭空间,氢气能	
起的特定危害	形成爆炸性混合物。在这种情况下,建议使用窒息剂灭火 	
Protective	As for any fire, evacuate the area and fight the fire from a safe distance. Wear a	
Equipment and	pressure-demand, self-contained breathing apparatus and full protective gear. Fight fire	
precautions for	from a protected location or a safe distance. Use NIOSH/MSHA approved full-face	
firefighters	self-contained breathing apparatus(SCBA) with full protective gear.	
消防队员的防	如果发生火灾,撤离该区域并在安全距离内灭火。戴上需要压力的自给式呼吸器和全套防	
护设备和注意	护装备。在有保护的地方或安全的距离灭火。使用NIOSH/MSHA认可的全面自给式呼吸器	
事项	(SCBA)和全套防护装备。	
NFPA	Health: 0 Flammability: 0 Instability: 0	
消防协会	健康: 0 易燃性: 0 不稳定性: 0	

Section 6 – Accidental Release Measures 第六部分—泄露应急处理

Personal Precautions,	Restrict access to area until completion of clean-up. Do not touch the
	·
protective equipment, and	spilled material. Wear adequate personal protective equipment as
emergency procedures	indicated in Section 8.
个人预防措施、防护装备和应	在清理工作完成之前,禁止任何人进入该区域。请勿触摸泄露的材料。穿戴
急程序	足够的个人防护装备,如第8章节所示。
Environmental Precautions	Prevent material from contaminating soil and from entering sewers or
环境保护措施	waterways.
	防止物质污染土壤和进入下水道或水道。
Methods and materials for Stop the leak if safe to do so. Contain the spilled liquid with dry sand	
Containment earth. Clean up spills immediately.	
方法和材料控制	处于安全,阻止泄露,可以用干砂或沙土来遏制液体泄露,立即清理泄漏。
Methods and materials for	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop
cleaning up	contaminated absorbent into an acceptable waste container. Collect all
清理的方法和材料	contaminated absorbent and dispose of according to directions in Section
	13. Scrub the area with detergent and water; collect all contaminated wash
	water for proper disposal.
	用惰性吸收剂(干燥的沙子或泥土)吸收溢出的材料。将被污染的吸收剂舀到
	可接受的废物容器中。收集所有被污染的吸收剂,并按照第 13 章节的说明
	处理。用清洁剂和水擦洗该区域;收集所有被污染的洗涤水,以适当的方式处
	理。



Section 7 – Handling and Storage 第七部分—操作处置与存储

Handling 操作	Don't handle Battery with metalwork. Do not open, dissemble, crush or burn battery. Ensure good ventilation/exhaustion at the workplace. Prevent formation of dust.Information about protection against explosions and fires: Keep ignition sources away-Do not smoke. 请勿用金属制品处理电池。请勿打开、分解、挤压或燃烧电池。确保工作场所通风良好。防止灰尘的形成。关于防止爆炸和火灾的信息:远离点火源-不要照题
Storage 存储	要吸烟。 If the Battery is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Battery periodically. 如果电池长期存放超过 3 个月,建议定期对电池充电。 3 months: -10°C~+40°C, 45 to 85%RH 3 个月: -10°C~+40°C, 相对湿度 45%-85%RH And recommended at 0°C~+35°C for long period storage. 长期存储在 0°C~+35°C 环境下 The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more. 存储后交付状态(满电时容量为 50%)的容量保持率为 80%以上 Do not store Battery haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects. 请勿将电池随意存放在盒子或抽屉中,以免电池之间相互短路或被其他金属物体短路。 Keep out of reach of children. 请置于儿童接触不到的地方。 Do not expose Battery to heat or fire. Avoid storage in direct sunlight. 请勿将电池置于高温或火中。避免储存在阳光直射的地方。
	Do not store together with oxidizing and acidic materials. 请勿与氧化性和酸性物质存放。

Section 8 – Exposure Controls and Personal Protection 第八部分-接触控制和个人防护

Engineering Controls	Use local exhaust ventilation or other engineering controls to control
工程控制	sources of dust, mist, fumes and vapor.
	使用当地的排气通风或其他工程控制,以控制灰尘,雾,烟雾和蒸汽的来源。
	Keep away from heat and open flame. Store in a cool, dry place.
	远离热源和明火。储存在阴凉、干燥的地方。
Personal Protective	Respiratory Protection: Not necessary under normal conditions.
Equipment	呼吸保护:正常情况下不需要。
个人防护装备	Skin and body Protection: Not necessary under normal conditions, Wear
	neoprene or nitrile rubber gloves if handling an open or leaking battery.
	皮肤和身体的保护:正常情况下不需要,处理打开或漏水的电池时,应戴氯丁
	橡胶或丁腈橡胶手套。
	Hand protection: Wear neoprene or natural rubber material gloves if



The second secon	i age o or is
	handling an open or leaking battery.
	手保护:在处理打开或泄漏的电池时,戴氯丁橡胶或天然橡胶材料的手套。
	Eye Protection:Not necessary under normal conditions, Wear safety
	glasses if handling an open or leaking battery.
	眼睛保护:正常情况下不需要,如果处理打开或泄漏的电池,请佩戴安全眼镜。
Other Protective Equipment	Have a safety shower and eye wash fountain readily available in the
其他防护设备	immediate work area.
	在直接的工作区域有一个安全的淋浴和洗眼喷泉.
Hygiene Measures	Do not eat, drink, or smoke in work area. Maintain good housekeeping.
卫生措施	请勿在工作区域内进食、饮水或吸烟。维护好管家.

Section 9 – Physical and Chemical Properties 第九部分–理化特性

	Form: Solid		
Physical	形态:固体		
	Appearance: White and Light Sliver		
State 物理状态	外观: 白色和矿石银长方体		
物理状态	Odor: Odorless		
	气味: 无气味		
Change in cond	dition	Not available.	
变化条件:		无数据可提供	
pH, with indicat	tion of the concentration	Not applicable	
pH,有浓度指示		不适用	
Melting point/fr	eezing point	Not available.	
熔点/凝固点		无数据可提供	
Boiling Point, ir	nitial boiling point and	Not available.	
Boiling range:		无数据可提供	
沸点、初沸点		儿数值可提供	
Flash Point		Not available.	
闪点		无数据可提供	
Upper/lower fla	mmability or explosive	Not available.	
limits		无数据可提供	
上/下燃烧或爆炸	作限值	// // // // // // // // // // // // //	
Vapor Pressure	e:	Not applicable	
蒸汽压		不适用	
Vapor Density:	(Air = 1)	Not applicable	
蒸汽密度: (空气=1)		不适用	
Density/relative density		Not available.	
密度/相对密度		无数据可提供	
Solubility in Water:		Insoluble	
水溶性		不能溶解	
n-octanol/water	partition coefficient	Not available.	
正辛醇/水分配系数		无数据可提供	



i age 9 of 10
130°C
Not available.
无数据可提供
Not applicable
不适用

Section 10 – Stability and Reactivity 第十部分-稳定性和反应性

Stability	The product is stable under normal conditions.
稳定性	该产品在正常条件下是稳定的。
Conditions to Avoid (e.g. static discharge, shock or vibration) 应避免的条件(如静电放电、冲击或振动)	Do not subject Battery to mechanical shock. Vibration encountered during transportation does not cause leakage, fire or explosion. Do not disassemble, crush, short or install with incorrect polarity. Avoid mechanical or electrical abuse. 请勿对电池进行机械冲击。运输过程中遇到的振动不会引起泄漏、火灾或爆炸。不要拆解、挤压、短路或安装错误的极性。避免机械或电气滥用。
Incompatible Materials	Not Available
异种材料	无数据可提供
Hazardous Decomposition Products	This material may release toxic fumes if burned or exposed to
危害分解物	fire
	这种材料如果被燃烧或暴露于火中,可能会释放出有毒气体
Possibility of Hazardous Reaction	Not Available
危险反应的可能性	无数据可提供

Section 11 – Toxicological Information 第十一部分-毒理学信息

Irritation	Risk of irritation occurs only if the cell is mechanically, thermally
刺激	or electrically abused to the point of compromising the enclosure.
	If this occurs, irritation to the skin, eyes and respiratory tract may
	occur.
	只有当电芯是受到机械,加热或电气滥用达到刺激点的风险。如果
	发生这种情况,皮肤、眼睛和呼吸道可能会受到刺激。
Sensitization	Not Available
敏化作用	无数据可提供



Control of the Contro	i age 10 of 10
Neurological Effects	Not Available
神经系统的影响	无数据可提供
Teratogenicity	Not Available
致畸性	无数据可提供
Reproductive Toxicity	Not Available
再生毒性	无数据可提供
Mutagenicity (Genetic Effects)	Not Available
诱变(遗传效应)	无数据可提供
Toxicologically Synergistic Materials	Not Available
协同材料毒理学	无数据可提供

Section 12 – Ecological Information 第十二部分–生态学信息

General note:	Water hazard class 1(Self-assessment): slightly hazardous for
通用信息	water.
	Do not allow undiluted product or large quantities of it to reach
	ground water, water course or sewage system.
	水危险等级 1(自评):对水有轻微危险。
	不允许未经稀释的产品或大量的产品进入地下水、水道或污水系
	统。
Anticipated behavior of a chemical	Not Available
product in environment/possible	无数据可提供
environmental impacted/ecotoxicity	
化学产品在环境/可能的环境预期的行为	
的一种生态毒性	
Mobility in soil	Not Available
土壤中移动性	无数据可提供
Persistence and Degradability	Not Available
持久性和降解性	无数据可提供
Bioaccumulation potential	Not Available
生物体内积累的潜力	无数据可提供
Other Adverse Effects	Not Available
其他不良反应	无数据可提供

Section 13 – Disposal Considerations 第十三部分–废弃处置

Product disposal recommendation	Observe local, state and federal laws and regulations.
产品处理建议	遵守当地、州和联邦法律法规。
Packaging disposal recommendation	Be aware discarded batteries may cause fire, tape the battery
包装处理建议	terminals to insulate them. Don't disassembly the battery.
	Completely discharge containers (no tear drops, no powder rest,



scraped carefully). Containers may be recycled or re-used. Observe local, state and federal laws and regulations.

废弃的电池可能引起火灾,请用胶带将电池端子绝缘。请勿拆卸电池。完全卸除容器(无泪滴,无粉歇,刮拭小心)。容器可以回收或重复使用。遵守当地、州和联邦的法律法规

Section 14 – Transport Information 第十四部分–运输信息

	0. 0.111. 0.4. 0.4. 0.4.
Label for conveyance	Class 9-Lithium Batteries, Cargo Aircraft Only
运输标签	第九类锂电池危险标记,仅限货机标记
UN number	UN3480 or UN3481
联合国货物编码	UN3480 或 UN3481
Proper shipping name	1) Lithium ion batteries;
运输名称	2) Lithium ion batteries packed with equipment;
	3) Lithium ion batteries contained in equipment.
	1) 锂离子电池单独运输;
	2) 锂离子电池和设备包装在一起;
	3) 锂离子电池内置于设备中
EmS No.	F A O I
应急措施编号	F-A, S-I
ICAO/IATA	Can be shipped by air in accordance with international Civil Aviation
国际民间航空组织/国际航空	Organization (ICAO), TI or International Air Transport Association (IATA)
运输协会	DGR Manual 65 th Packing Instruction Section I(or Section IA) of Packing
	Instruction 965~967 for transportation.
	可根据民用航空组织(ICAO),TI 或国际航空运输协会(IATA)DGR 手册
	65 版本中 PI965~967 包装说明 Section I(or Section IA)的规定进行空运。
IMDG CODE	Shipping may be done in accordance with the P903 of the IMDG
国际海运危险货物规则	CODE(Amdt. 41-22)Edition.
	可根据 IMDG CODE(Amdt. 41-22)版的 P903 条相关规定进行海运。
DOT	Other requirements for the US Department of Transportation (DOT)
美国运输部	Subchapter C, Hazardous Materials Regulations if shipped in compliance
	with 49 CFR 173.185.
	美国运输部(DOT)有害物质规则 C 分章节中的其他规定,运输符合要求 49
	CFR 173.185。
ADR/ADN	Transport Requirements for United Nations Economic Commission for
欧洲国际陆运危险货物协定/	Europe (UNECE) ADR/ADN, Applicable as from 1 January 2019.
关于陆水道国际运输危险货	自 2019 年 1 月 1 日起需符合联合国欧洲经济委员会 (UNECE) ADR/ADN 的
物的欧洲协定	运输要求。

In addition, to be permitted in transport each lithium cell and battery types must have passed the applicable tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria.

此外每个电芯和电池类型都必须通过联合国《关于危险货物运输的建议书试验和标准手册》第 38.3 章节规定的适用测试。



Section 15 - Regulation Information

第十五部分-法规信息

Law information:

法律信息:

《Dangerous Goods Regulations》

《危险货物规则》

《Recommendations on the Transport of Dangerous Goods Model Regulations》

《关于危险货物运输的建议书规章范本》

《Recommendations on the Transport of Dangerous Goods Manual of Tests and Criteria》

《关于危险货物运输的建议书试验和标准手册》

《International Maritime Dangerous Goods》

《国际海运危险货物规则》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《危险货物安全运输技术指南》

《Classification and code of dangerous goods》

《危险货物分类和品名编码》

《Occupational Safety and Health Act》(OSHA)

《职业安全与健康法》(OSHA)

《Toxic Substance Control Act》(TSCA)

《有毒物质控制法》(TSCA)

《Consumer Product Safety Act》(CPSA)

《消费品安全法》(CPSA)

《Federal Environmental Pollution Control Act》(FEPCA)

《联邦环境污染控制法》(FEPCA)

《Resource Conservation and Recovery Act》(RCRA)

《资源保护与恢复法案》(RCRA)

In accordance with all Federal. State and local laws.

符合所有联邦, 州和地方法律。

Section 16 – Other Information 第十六部分—其他信息

The information above is believed to be accurate and represents the best information currently available to us. However, Dongguan Lepont Testing Service Co., Ltd. makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

The data/information contained herein has been reviewed and approved for general release on the basis

Test Report Form No.: MSDS-E



Report No./报告编号: LP24080152C01-01 Page 13 of 13

Test Report Form No.: MSDS-E

that this document contains no export controlled information.

上述信息被认为是准确的,并代表了我们目前所能获得的最佳信息。但东莞市力邦检测服务有限公司不保证该等信息的适销性或任何其他明示或暗示的保证,我们也不承担因使用该等信息而产生的任何责任。用户应自行进行调查,以确定信息是否适合其特定目的。虽然在准备本文所包含的数据时已采取了合理的预防措施,但仅供您参考、考虑和调查。本材料安全数据表为安全操作和使用本产品提供了指南,它不会也不能对所有可能的情况提供建议,因此应该评估您使用本产品的具体情况,以确定是否需要额外的预防措施。本文件中所包含的数据/信息已经过审核并批准发布,基于本文件不包含任何受出口管制的信息。